

Mr/Mrs/Ms \_\_\_\_\_ Model \_\_\_\_\_ Reg No \_\_\_\_\_

Invoice/Job No \_\_\_\_\_ Odometer reading \_\_\_\_\_ VIN \_\_\_\_\_

Service type	<b>A</b>	<b>1st</b>	<b>B</b>	<b>C</b>	<b>B</b>	<b>C</b>	<b>B</b>	<b>C</b>
Years / Miles x 1000	0	5/6	1/12	2/24	3/36	4/48	5/60	6/72
<b>A Service = 1st 6000 miles only</b>								

For full details regarding the operations contained in this maintenance check sheet, please refer to the workshop manual.

## MAINTENANCE CHECK SHEET

### A 1st B C Preliminary

1    Before commencing work, check for any outstanding service actions

### VEHICLE INTERIOR AND EXTERIOR

- 2    Fit vehicle protection kit
- 3    1 Yr  Replace alarm handset batteries - Every 12 months
- 4    Check handbrake operation and adjust if necessary.
- 5    Check lamps, horns and system warning indicators
- 6    Check screen for damage and operation of wipers and washers - Adjust washers if required
- 7    Check seatbelt operation, seatbelts and airbag module covers for damage.
- 8    Check air conditioning system operation - If applicable
- 9    Lubricate locks, strikers, latches, door hinges and door checks

### ENGINE BAY

- 10    Check battery connections and charge condition.
- 11    Check and top up brake, power steering and screen washer fluid levels
- 12    Check brake servo vacuum pipe condition
- 13    Check coolant level and top up if necessary
- 14    Check and record anti freeze content  **Concentration % or degrees C** - ( Concentration must be corrected if below 50% ) - Use tool No 26R0003
- 15    Inspect air conditioning system hoses and sight glass
- 16    Check auxiliary drive belts, tension and condition
- 17    2/24 Replace air cleaner element - **Every 24,000 miles**
- 18    1/12 Spark plugs, remove, clean and adjust - **Every 12,000 miles**
- 19    2/24 Replace spark plugs - **Every 24,000 miles**

**A 1st B C With Vehicle on Lift**



# CityRover

- 20  5/60 Replace camshaft drive belt - **Every 60,000 miles or 5 years, whichever is the sooner**
- 21  2/24 Replace antifreeze using vacuum fill process - First change from Glycol to OAT  
**24,000 miles or 2 years, whichever is the sooner.** - Use tool No 26R002
- 22  Replace antifreeze using vacuum fill process - Second and subsequent changes  
**Every 48,000 miles or 4 years after first change, whichever is the sooner** - Use tool No 26R002
- 23  Check anti freeze content after antifreeze change  Concentration % or degrees C  
**( Concentration must be corrected if below 50% )** - Use tool No 26R003
- 24  2/24 Replace manual gearbox oil - **Every 24,000 miles or 2 years, whichever is the sooner**
- 25  1st 6 Replace engine oil and filter - First change at 6000 miles - second change at 12,000 miles, subsequent changes at 12,000 mile intervals thereafter
- 26  5/60 Replace fuel filter - **Every 60,000 miles or 5 years, whichever is the sooner**
- 27  Check wheel bearings, drive shafts and gaiters
- 28  Mark relative hub and wheel position and remove front and rear road wheels, check wheels for damage.
- 29  Check tyres for damage, uneven wear and tread depth including spare (mm)  
 LHF  RHF  RHR  LHR  Spare
- 30  Visually check front and rear brake pads/linings, discs/drums, calipers/cylinders, hoses and pipes for wear or damage
- 31  Inspect for condition and evidence of leakage from fuel, transmission and engine systems.
- 32  Inspect exhaust system and heat shields.
- 33  Inspect suspension and steering systems for signs of leaking or wear.
- 34  2/24 Replace brake fluid - **Every 24,000 miles or 2 years, whichever is the sooner. - CHARGED SEPARATELY**
- 35  Apply anti sieze compound to wheel hub and refit road wheels to original hub position, apply correct torque to wheel bolts.

**VEHICLE EXTERIOR ( Stage 2 )**

- 36  Check tyre pressures and adjust if necessary, including spare (bar)  
 LHF  RHF  RHR  LHR  Spare

**15 YEAR REPLACEMENT - AIRBAGS**

Replace airbag module(s) Seat belt pre tensioners and rotary coupler - **CHARGED SEPARATELY**

**AFTER EACH SERVICE**

- 38  Annual corrosion/cosmetic inspection - **Using annual corrosion inspection sheet**
- 39  Carry out road test, check for the correct function of all vehicle systems

The maintenance items listed are those recommended for vehicles operating under normal driving, road and climatic conditions.  
More frequent attention may be necessary if the vehicle is subject to stop/start operation, extremes of temperature, dusty conditions or frequent towing of trailers

Service check completed, cosmetic/corrosion inspection check completed and service portfolio book stamped.

Name \_\_\_\_\_ Signature \_\_\_\_\_ Date \_\_\_\_\_